

Index
File No.

T 3 S R. 10 W
Merid. Will.


CORNER RECORD (SEARCH)
(Ref. FSM 7151.4)

R.D. Hebo County Tilla
N.F. Siuslaw State Ore.

Tract or
Survey No.

Cor.
No. P-12

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND
BY RECORD, JACK SHEPPARD ORLS # 180 PROPORTIONED
THIS CORNER THE YEAR 1947.

He set 2x2 WHITE STAKE & MKD.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES

HE MARKED
42" FIR, N. 20° 06' W, 11 1/2 FT. MKD. 1/6 SBT.
38" FIR, S. 85° 09' E, 56 25 FT. MKD. 1/6 SBT.

PHOTO IDENTIFICATION DATA

Photo No.

Filed At.

Object Ident.

Ident. By

Signature

PLANE COORDINATE POSITION DATA

State Zone

X

Y

Estab. By

Agency

I FOUND 2x2" WHITE STAKE 10" ABOVE GROUND IN FAIR

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
CONDITION. SET ALUMINUM POST 1 FT. N.E. OF CORNER WITH
LOCATION & BOUNDARY TINS ATTACHED.

FOUND 42" FIR STUMP, N. 22° W, 11 1/2 FT. WITH VISIBLE
SCRIBE MARKS 1/6 SBT. PAINT FACE RED & PUT BT
SIGN ON STUMP.

THE S.E. BT IS IN PLACE BUT ALL MARKS ARE RATTED AWAY.

Signature

Title

Divis

Headquarters

Date

JO-52 (3/68)

Leonard Whitman Forestry Tech Junior Hebo

6-25-69

CORNER RECORD (PERPETUATION)

DESCRIBE NEW MONUMENT SET OR WORK DONE

SERVE EXISTING MONUMENT

I PULL UP THE 2x2" WHITE POST AND SET 3/4 GALV. PIPE IN ITS PLACE
SET WHITE POST ALONGSIDE PIPE.

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

MARK 2 NEW BT'S;

46" FIR, S. 86° 30' E, 55 3/4 FT. MKD. CE 1/6 SBT.

31" SPRUCE, N. 19° W, 30 3/4 FT. MKD. CE 1/6 SBT.

PUT BT SIGNS ON WITH

Leonard Whitman, Tilla, Co. Dep. surveyor, 6-25-69

Work Done By

Title

Date

State Registration No.
or Agency

Certified Cor. Record Prepared ? Yes No

Filed At

Date

REMARKS

Leonard Whitman is a deputy C.S. qualified to re witness &
re-measurement positive existent old corners.

12/23/70

G. Karla C.S.

File No.

T 3 S R. 10 W M. WILL

Tract or Surv. No.

21

CE 1/6